

WE CLAIM

Claim 1.

A walker comprising:

a first generally U-shaped frame member having a first front
5 leg and a first rear leg;

a second generally U-shaped frame member having a second
front leg and a second rear leg;

a cross member joining the first front leg with the second
front leg;

10 a first castor rotatably attached on the first front leg
such that the first castor faces the second front leg; and

a second castor rotatably attached on the second front leg
such that the second castor faces the first front leg.

Claim 2.

15 The walker as in claim 1 wherein the first castor is
attached to the first front leg by passing a first axial bolt
through the first castor and into the first front leg wherein the
first axial bolt is received within a first screw boss and
wherein the second castor is attached to the second front leg by
20 passing a second axial bolt through the second castor and into
the second front leg wherein the second axial bolt is received
within a second screw boss.

Claim 3.

The walker as in claim 2 further comprising:

a lower bracket attached to the first front leg, the lower bracket having a base and an annular flange;

an upper bracket attached to the first front leg above the lower bracket, the upper bracket being a resilient C-clip such
5 that the C-clip is longitudinally aligned with the annular flange; and

wherein a cane is adapted to be removably received within the upper bracket and to rest on the base of the lower bracket.

Claim 4.

10 The walker as in claim 1 further comprising:

a lower bracket attached to the first front leg, the lower bracket having a base and an annular flange;

an upper bracket attached to the first front leg above the lower bracket, the upper bracket being a resilient C-clip such
15 that the C-clip is longitudinally aligned with the annular flange; and

wherein a cane is adapted to be removably received within the upper bracket and to rest on the base of the lower bracket.

Claim 5.

20 A walker comprising:

a first generally U-shaped frame member having a first front leg and a first rear leg;

a second generally U-shaped frame member having a second front leg and a second rear leg;

a cross member joining the first front leg with the second front leg;

a lower bracket attached to the first front leg, the lower bracket having a base and an annular flange;

5 an upper bracket attached to the first front leg above the lower bracket, the upper bracket being a resilient C-clip such that the C-clip is longitudinally aligned with the annular flange; and

wherein a cane is adapted to be removably received within
10 the upper bracket and to rest on the base of the lower bracket.

Claim 6.

The walker as in claim 5 further comprising:

a first castor rotatably attached to the first front leg;

and

15 a second castor rotatably attached to the second front leg.